Datasheet

TRI-COLOUR LED Downlights







DLI90TRIBE DLI90TRIBL DLI90TRIBC

Cat no.	DLI90TRIBL, DLI90TRIWE, DLI90TRIBC	DLI110TRIWE	DLI150TRIWE
Supply Voltage	230 - 240V a.c. 50Hz		
Input Power	7W		10W
Colour Rendering Index (CRI)	80+		
Beam Angle	900	95º	
Lifespan	up to 35,000 hrs		
Dimmable	Trailing Edge Dimmer		
Insulation Rating	IC-4 and IC-F		
IP Rating	IP44		
Ceiling Cutout Size	Ø90mm	Ø 110mm	Ø150mm
Depth into Ceiling	72mm		80mm
Fascia Size	Ø110mm	Ø138mm	Ø175mm
Fascia Colour	Black (BL), White (WE), Brushed Chrome (BC)		

TRI-COLOUR LED Downlights

CAT NO. DLI90TRIWE, DLI90TRIBL, DLI90TRIBC, DLI110TRIWE, DLI150TRIWE







- •Light Colour Selector lets you easily switch between Warm (3,000K), Cool (4,000K) and Natural (5,000K) light temperature
- •Integrated dimmable driver compatible with trailing edge dimmers
- •Smooth dimming range
- •Suitable for 90mm, 110mm and 125mm cut-outs
- •Fitted with 1m flex and plug
- •Suitable for outdoor undercover areas (IP44 rating)
- •2,500V electrical surge protection
- •Screw-less terminal cover for easy, hard-wired connection
- High quality flame retardant plastic construction
- •IC-F and IC-4 insulation rating This downlight can be fully covered and abutted by insulation material
- •Up to 35,000h lifespan

Single product		
Cat No	Single Barcode	
DLI90TRIWE	9321001463733	
DLI90TRIBC	9321001488224	
DLI90TRIBL	9321001488200	
DLI110TRIWE	9321001463740	
DLI150TRIWE	9321001463757	

Outer box (Qty 24)		
Cat No	Barcode	
DLI90TRIWE	9321001463764	
DLI90TRIBC	9321001488231	
DLI90TRIBL	9321001488217	
DLI110TRIWE	9321001463771	
DLI150TRIWE	9321001463788	