

Data Sheet

Twin LED Floodlight with Sensor

CAT NO. LFS013KBL



Cat No	LFS013KBL
Description	Twin LED Floodlight with Sensor
Voltage supply	230 – 240 Va.c 50Hz
Power consumption	29W
Lamps	2 x 14W PAR38
Lumens	2 x 1100 lm
Maximum load	2 x 150W PAR38
Weatherproof	IP44
Operating temperature	-10°C to 50°C
Detection circuitry	PIR (Passive Infrared)
Detection range / angle	12m / 120°
Time adjustment	(10±5) seconds to (4±1) minutes
Recommended mounting height	> 2m
Replacement LED lamp	LPAR38013K

Twin LED Floodlight with Sensor

CAT NO. LFS013KBL



- Weatherproof IP44 LED Twin LED Floodlight with Sensor
- Security – instantly reacts to intruders by turning lights on
- Ideal for outdoor areas, front and back porches, deck and patio, secluded walkways and driveway.
- Adjustable time delay and lux levels

Single product			
Cat No	Dimensions	Weight	Barcode
LFS013KBL	405W x 120H x 148D mm	1.042kg	9321001434788

Outer box (QTY 10)			
Cat No	Dimensions	Weight	Barcode
LFS013KBL	620W x 420H x 315D mm	12kg	9321001434795

Replacement LED globe	LPAR38013K
Wattage	13.6W
Total Lumens output	1100 lm

HPM Legrand - AUS
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.