

Data Sheet

Twin USB Charging Station with Lead

CAT NO. PS2USB



Product specifications	
Cat No	PS2USB
USB charging capacity	2 x 2.1A
Voltage	230-240V a.c. 50Hz
Surge protection	150 joules
Overload protection	2400W
Standby power consumption	<0.15W

Twin USB Charging Station with Lead

CAT NO. **PS2USB**



- Maximum charging speed.
- 4.2A charging capacity: Charge up to two tablets simultaneously.
- 1.5m lead.
- Ideal for people on-the-go for charging multiple electronic devices.

Single product			
Cat No	Barcode	Dimensions	Weight
PS2USB	9321001427179	105 x 162 x 52mm	0.265kg

Inner box (Qty 6)			
Cat No	Barcode	Dimensions	Weight
PS2USB	9321001427315	496 x 220 x 62mm	1.9kg

Outer box (Qty 36)			
Cat No	Barcode	Dimensions	Weight
PS2USB	9321001427322	506 x 450 x 196mm	12kg

USB Charging Capacity		
Standard USB Charger	1A	Charge 1 smartphone
	2.1A	Charge 2 smartphones or Charge 1 tablet
	3.1A	Charge 2 smartphones or Charge 1 tablet & 1 smartphone
HPM USB Charger	4.2A	Charge 2 smartphones or Charge 1 tablet & 1 smartphone or Charge 2 tablets

Table based on standard charging capacity of 1A for smartphones and 2.1A for tablets.

HPM Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.