Datasheet

SERENE DC CEILING FAN-1220MM, 48"

CAT. NO. CF12DC4BWE



























Fan Speed	RPM*	Power (Watts)	Airflow (m³/h)
1	110	5	4500
2	137	8	5700
3	169	12	6900
4	198	18	8400
5	230	26	9900
6	260	40	11400

^{*}RPM: Rotations Per Minute





PRODUCT SPECIFICATIONS

Cat. No.	CF12DC4BWE		
Colour/Finish	White		
Supply Voltage	230-240 V ~ 50 Hz		
Motor Type	DC (Direct Current)		
Maximum Power	40 W		
Maximum RPM	260 RPM		
Maximum Airflow	11400 m³/h		
Blade Pitch	11.5°		
Body and Canopy Construction	ABS plastic (rust free^)		
Blade Material	ABS plastic (rust free^)		
Blade Size	1220 mm, 48"		
Number of Blades	4		
Ceiling Install	Hang sure canopy mounting (slope up to 13°)		
Recommended Height	There should be at least 2.1 m between the lowest point of the ceiling fan blades and the floor		
Remote Control	6 speed fan controller with 3 timers, forward/reserve mode, natural wind mode and fan ON/OFF + wall mounted holder		
Includes	Motor assembly, 4 x ABS plastic blades, screw pack, fan remote control, 2x AAA batteries, mounting bracket, instruction manual		

[^]Body, canopy and blades are made from ABS plastic, rust free does not apply to the metal downrod.

Datasheet

SERENE DC CEILING FAN-1220MM, 48"

CAT. NO. CF12DC4BWE



FEATURES AND BENEFITS


- Powerful 40 W DC motor.
- DC motor is more powerful, quieter and uses less energy than an AC motor.
- ABS plastic ceiling fans are suitable for indoor or undercover outdoor areas not exposed to the weather.
- Body, canopy and blades are made from ABS plastic, making them rust free^.
- Moulded ABS plastic blades for high strength and durability, which are easy to clean.
- Pre-wired replaceable downrods for easy height extension, available in 750 mm and 1500 mm lengths.
- Coastal rated to withstand water damage due to salt found in the air.
- Fast connect wiring system and quick-fit blades system for ease and reduction of installation time.
- Reversible summer and winter mode to save energy for use all year round.
- Sleek and modern ceiling fan design with curvaceous blades to compliment any space.
- Natural wind mode varies the fan speed to simulate a natural breeze effect.
- 6 speed remote controller with timer included for greater control.

HOW TO CHOOSE THE RIGHT CEILING FAN SIZE

Room size (m²)	Up to 7 m²	7 m² to 13 m²	13 m² to 20 m²
Recommended Fan Size (mm)	920 mm to 1220 mm 1220 mm to 1320 mm		1320 mm to 1420 mm
Recommended Fan Size (inches)	36" or 48"	48 " or 52"	52" or 56"

REGULATION REQUIREMENT

The Australia & New Zealand standard implies that the lowest point of the fan blades must be installed at least 2.1 m from the floor and the blades at least 300 mm from the nearest wall.





SHIPPING

Single Product					
Cat. No.	Barcode	Packaging Dimensions (mm)	Product Weight (kg)		
CF12DC4BWE	9321001516248	595 x 330 x 317	6.0		

Legrand - Australia 1300 369 777 www.hpm.com.au ABN 31 000 102 661

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.



[^] Rust free does not apply to the metal downrod.